



# NLS-HR5280-BT

## WIRELESS 2D BARCODE SCANNER

### FEATURES

○ **Outstanding Performance**

Equipped with an outstanding CPU, this CPU-based scanner can effortlessly capture high-density, high volume and distorted barcodes printed on paper or displayed on screen.

○ **Durable Construction**

The scanner is built into an IP54-sealed and drop resistant (1.8m) housing without moving parts and fortifies itself.

○ **Powerful Data Editing Function**

The HR5280-BT allows to customize decoding mode flexibly through preset.

○ **Low Consumption and Great Compatibility**

The low consumption of HR5280-BT reduces connection issues and maximizes the compatibility for diverse applications.

○ **Reliable and Stable Wireless Communication**

Adopting the latest Bluetooth which is strong anti-interference and stable to transmit the data.



CMOS



1D Barcode



2D Barcode



Drop



IP 54



USB



RS232



Bluetooth



2400mAh

# NLS-HR5280-BT

## Performance

Image Sensor		1280×800 (megapixel) CMOS
Illumination		White LED
Aiming		650nm laser diode
Symbologies	2D	PDF417, Micro PDF 417, QR Code, Micro QR Code, Data Matrix, Aztec, Maxicode, Chinese Sensible Code, GM Code, Code One
	ID	EAN-13, EAN-8, UPC-A, UPC-E, Coupon, Febraban, ISSN, ISBN, Codabar, Code 128, Code93, ITF-6, ITF-14, China Post 25, Interleaved 2 of 5, Industrial 25, Standard 25, Matrix 25, GSI Databar(RSS), GSI-128 (UCC/EAN-128), GSI Composite(EAN UCC Composite), Code 39, Code 11, MSI-Plessey, Plessey, AIM 128, ISBT 128, Code 49, Code 16K
	Postal	USPS Postnet, USPS Intelligent Mail, Royal Mail, KIX Post, Australian Postal
Resolution*		≥3mil
Typical Depth of Field*	EAN-13	50mm-555mm (13mil)
	Code 39	110mm-240mm (5mil)
	PDF 417	90mm-210mm (6.7mil)
	Data Matrix	90mm-190mm (10mil)
	QR Code	40mm-360mm (15mil)
Scan Angle**		Pitch: ±55°, Roll: 360°, Skew: ±55°
Field of View		Horizontal 42°, Vertical 28°
Min Symbol Contrast*		20%

## Wireless

Communication Mode	Synchronous, asynchronous and batch mode
Radio Technology	Bluetooth 5.0
Communication Distance	50m/164ft (direct line of sight in open air)
Memory Capacity	≥15000 pieces of Code 128 (20 byte of each Code 128)
Battery	2400 mAh lithium-ion battery
Expected Charge Time	4 hours (with power adapter)
Expected Battery Life	12 hours of continuous operation (scan once per 6 seconds)

## Physical

Interface	RS-232, USB
Operating Voltage	5VDC±5%
Dimensions (L×W×H)	Scanner: 172.5×77.5×95.5mm Cradle: 194.0×90.5×68mm
Weight	Scanner: 227g
Notification	Beep, LED indicator, vibration

## Environmental

Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Battery Charge Temperature	0°C to 45°C (32°F to 113°F)
Humidity	5%-95% (non-condensing)
ESD	±15 KV (air discharge); ±8 KV (direct discharge)
Drop	Scanner: 1.8m/5.9ft Cradle: 1m/3.3ft
Sealing	Scanner: IP54

## Certificates

Certificates & Protection	FCC Part15 Class B, CE EMC Class B, RoHS
---------------------------	--

\*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

\*\*Test conditions: Scan Distance= (min. DOF + max. DOF) / 2; T=23°C; Illumination=300lux using incandescent lamp;

ID: EAN-13 (13mil).

Specifications are subject to change without notice.

Version: V1.5

### Newland AIDC

Add: No.1 Rujiang West Rd.,  
Mawei, Fuzhou, Fujian 350001, China  
Tel: +86-591-83979500  
Fax: +86-591-83979216  
Email: info@nlsan.com  
Web: www.newlandaidc.com

### Asia Pacific

Taiwan:  
Add: 7F-6, No. 268, Liancheng Rd.,  
Jhonghe Dist. 235, New Taipei City, Taiwan  
Tel: +886 2 7731 5388  
Email: info@nlsan.com

### Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,  
The Netherlands  
Tel: +31 (0) 345 87 00 33  
Email: sales@newland-id.com  
Tech Support: tech-support@newland-id.com

### North America & Latin America

Add: 46559 Fremont Blvd.,  
Fremont, CA 94538, USA  
Tel: +1 510 490 3888  
Fax: +1 510 490 3887  
Email: info@nlsan.com